



The Safest Tanks in Motion

Product Specification Sheet

DIESEL TRANSFER UNITS

DieselCaptain™ 200L

Low Profile with 40L/min Dieselflo Pump and 4m x 3/4" Hose

CODE: DUL0200LD040V1

The Internationally Certified DieselCaptain™ is your ultimate and reliable refueling partner! This poly diesel fuel tank is equipped with world class pumps, hoses and auto shut off nozzles, so you can be assured your diesel refueling is done quickly and efficiently.



- » Manufactured from specifically formulated diesel grade polyethylene that meets International Regulation ECE R34.01 requirements
- » All TransDiesel tanks comply with AS1940-2004 and AS2809.2-2008
- » Low profile design
- » 12 Volt 40L/min Dieselflo pump
- » 3/4" auto shut off nozzle
- » Strong poly lid to protect pump compartment
- » Locking latch for lid, to protect your investment
- » Ergonomic lifting handles for ease of transport
- » 4m x 3/4" hose for extra reach
- » 3/4" drain bung
- » Moulded with our unique aluminium ring for incredible strength, this multi seal system keeps the rain out, and your diesel in

SPECIFICATIONS

Tank Material	Polyethylene
Lid Diameter	N / A
Capacity (brim full)	200 Litres
Tare Weight	37 kg
(W) Full of Water	N / A
Dimensions (L W H)	1150 x 820 x 565 mm
Tank Warranty	15 Years
Pump Warranty	1 Year

www.tti.com.au

1800 816 277